



Lifting Eye Starpoint RUD VRS

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly available, look type VRS-F

Safety factor: 4:1

| Код товара | WLL ton | B mm | C mm | D mm | E mm | G mm | I mm | K mm | L mm | M mm | N mm | T mm | Bec kg |
|--------------|---------|------|------|------|------|------|------|------|------|------|------|------|--------|
| 421100031270 | 0,3 | 11 | 9 | 25 | 25 | 30 | 16,3 | 47 | 12 | M8 | 6 | 35 | 0,11 |
| 421100041270 | 0,4 | 11 | 9 | 25 | 25 | 30 | 16,3 | 47 | 15 | M10 | 6 | 35 | 0,11 |
| 421100081270 | 0,75 | 13 | 10 | 30 | 30 | 34 | 19,8 | 56 | 18 | M12 | 8 | 42 | 0,19 |
| 421100081275 | 0,75 | 13 | 10 | 30 | 30 | 30 | 34 | 19,8 | 56 | 18 | M14 | 8 | 0,2 |
| 421100151270 | 1,5 | 15 | 13 | 35 | 36 | 40 | 23,5 | 65 | 24 | M16 | 10 | 49 | 0,32 |
| 421100231270 | 2,3 | 17 | 16 | 40 | 41 | 50 | 29,3 | 76 | 30 | M20 | 12 | 58 | 0,54 |
| 421100321270 | 3,2 | 20 | 19 | 49 | 51 | 60 | 35 | 92 | 36 | M24 | 14 | 70 | 0,86 |
| 421100451270 | 4,5 | 26 | 24 | 60 | 66 | 75 | 44 | 114 | 45 | M30 | 17 | 87 | 1,5 |
| 421100701270 | 7 | 32 | 29 | 73 | 76 | 98 | 53 | 135 | 54 | M36 | 22 | 104 | 3,3 |

Blueprint

