



Lifting Eye Starpoint VRS-F with Variable Length

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

Safety factor: 4:1

| Код товара | WLL | B mm | C mm | D mm | E mm | G mm | I mm | K mm | L mm | M mm | N mm | T mm |
|--------------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 421100041110 | 0,4 | 11 | 9 | 25 | 25 | 30 | 16,3 | 47 | 16-70 | M10 | 6 | 35 |
| 421100081110 | 0,75 | 13 | 10 | 30 | 30 | 34 | 19,8 | 56 | 18-150 | M12 | 8 | 42 |
| 421100151110 | 1,5 | 15 | 13 | 35 | 36 | 40 | 23,5 | 65 | 35 | M16 | 10 | 49 |
| 421100151115 | 1,5 | 15 | 13 | 35 | 36 | 40 | 23,5 | 65 | 120 | M16 | 10 | 49 |
| 421100151116 | 1,5 | 15 | 13 | 35 | 36 | 40 | 23,5 | 65 | 24-120 | M16 | 10 | 49 |
| 421100231110 | 2,3 | 17 | 16 | 40 | 41 | 50 | 29,3 | 76 | 120 | M20 | 12 | 58 |
| 421100231115 | 2,3 | 17 | 16 | 40 | 41 | 50 | 29,3 | 76 | 160 | M20 | 12 | 58 |
| 421100231116 | 2,3 | 17 | 16 | 40 | 41 | 50 | 29,3 | 76 | 30-160 | M20 | 12 | 58 |
| 421100321110 | 3,2 | 20 | 19 | 49 | 51 | 60 | 35 | 92 | 36-140 | M24 | 14 | 70 |
| 421100451110 | 4,5 | 26 | 24 | 60 | 66 | 75 | 44 | 114 | 45-190 | M30 | 17 | 87 |

Blueprint

