



## Lifting Eye Starpoint VRS-F with Variable Length

### Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

**Safety factor:** 4:1

Код товара	WLL	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	M mm	N mm	T mm
421100041110	0,4	11	9	25	25	30	16,3	47	16-70	M10	6	35
421100081110	0,75	13	10	30	30	34	19,8	56	18-150	M12	8	42
421100151110	1,5	15	13	35	36	40	23,5	65	35	M16	10	49
421100151115	1,5	15	13	35	36	40	23,5	65	120	M16	10	49
421100151116	1,5	15	13	35	36	40	23,5	65	24-120	M16	10	49
421100231110	2,3	17	16	40	41	50	29,3	76	120	M20	12	58
421100231115	2,3	17	16	40	41	50	29,3	76	160	M20	12	58
421100231116	2,3	17	16	40	41	50	29,3	76	30-160	M20	12	58
421100321110	3,2	20	19	49	51	60	35	92	36-140	M24	14	70
421100451110	4,5	26	24	60	66	75	44	114	45-190	M30	17	87

# Blueprint

