

## Wire rope Dyform Bristar 8

### Product information



Dyform Bristar 8 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profile between the 8 outer strands and the rope core for cranes and industrial applications including mobile, crawler and tower cranes.

**Standard:** EN 12385-4

**ISO 4309 Rope Category No:** 10-17mm **RCN.04**, 18-34mm **RCN.09**, 36-50mm **RCN.11**

**Marking:** According to standard

**Standard:** EN 12385-4

**Fill factor:** 0.68

**RCN:** 04

Код товара	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Bec kg/100m
103102804270659	28	1 960	Galvanized	sZ	691	-	SupplierStandard	367
103103203270709	32	1 960	Galvanized	zS	903	-	SupplierStandard	482
103103404270709	34	1 960	Galvanized	sZ	1 020	-	SupplierStandard	544
103103604270709	36	1 960	Galvanized	sZ	1 145	-	SupplierStandard	613
103103603270709	36	1 960	Galvanized	zS	1 145	-	SupplierStandard	613
103103804270709	38	1 960	Galvanized	sZ	1 300	-	SupplierStandard	685
103103803270709	38	1 960	Galvanized	zS	1 300	-	SupplierStandard	685