


## Wire rope Dyform Bristar 8

### Product information



Dyform Bristar 8 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profile between the 8 outer strands and the rope core for cranes and industrial applications including mobile, crawler and tower cranes.

**Standard:** EN 12385-4

**ISO 4309 Rope Category No:** 10-17mm **RCN.04**, 18-34mm **RCN.09**, 36-50mm **RCN.11**

**Marking:** According to standard

**Standard:** EN 12385-4

**Fill factor:** 0.68

**RCN:** 04

| Код товара      | Rope Diameter<br>mm | Tensile strength<br>N/mm <sup>2</sup> | Min. Breaking force<br>kN. | Finish     | Bec<br>kg/100m |
|-----------------|---------------------|---------------------------------------|----------------------------|------------|----------------|
| 103102804270659 | 28                  | 1 960                                 | 691                        | Galvanized | 367            |
| 103103604270709 | 36                  | 1 960                                 | 1 145                      | Galvanized | 613            |
| 103103603270709 | 36                  | 1 960                                 | 1 145                      | Galvanized | 613            |
| 103103804270709 | 38                  | 1 960                                 | 1 300                      | Galvanized | 685            |
| 103103803270709 | 38                  | 1 960                                 | 1 300                      | Galvanized | 685            |
| 103103404270709 | 34                  | 1 960                                 | 1 020                      | Galvanized | -              |
| 103103203270709 | 32                  | 1 960                                 | -                          | Galvanized | -              |