


Wire rope Dyform Bristar 8

Product information



Dyform Bristar 8 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profile between the 8 outer strands and the rope core for cranes and industrial applications including mobile, crawler and tower cranes.

Standard: EN 12385-4

ISO 4309 Rope Category No: 10-17mm **RCN.04**, 18-34mm **RCN.09**, 36-50mm **RCN.11**

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.68

RCN: 04

Код товара	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Bec kg/100m
103102804270659	28	1 960	Galvanized	sZ	691	-	SupplierStandard	367
103103203270709	32	1 960	Galvanized	zS	-	-	SupplierStandard	-
103103404270709	34	1 960	Galvanized	sZ	1 020	-	SupplierStandard	-
103103604270709	36	1 960	Galvanized	sZ	1 145	-	SupplierStandard	613
103103603270709	36	1 960	Galvanized	zS	1 145	-	SupplierStandard	613
103103804270709	38	1 960	Galvanized	sZ	1 300	-	SupplierStandard	685
103103803270709	38	1 960	Galvanized	zS	1 300	-	SupplierStandard	685