

HJ H Gravity Return Hydraulic Cylinder

Product information



Double acting, hydraulic return cylinder.

- Max. working pressure: 720 bar/ 72 Mpa
- Acting type: double
- Return type: hydraulic
- Usable in all positions
- Protected against ejection of plunger
- Protection against overpressure on return side
- Flat saddle. Prevents damage to the plunger and is easy to replace with tilting saddle.

Standard supplied with:

- High Flow female coupler A 118
- Flat saddle that prevents damage to the plunger and is easy to replace with tilting saddle.

Available on request:

- Cylinders manufactured in conformity with customer specifications
- Collar thread
- Base mounting holes

Код товара	Код	WLL ton	Stroke mm	Closed height mm	Capacity kN/t	I type	Вес kg
5211100122002	HJ 50 H 15	50	150	282	510.3 / 52	I2	27
5211100122022	HJ 50 H 30	50	300	463	510.3 / 52	I2	44
5211100122009	HJ 100 H 5	100	50	170	1029.3 / 105	I1	29
5211100122052	HJ 100 H 15	100	150	309	1029.3 / 105	I1	53
5211100122054	HJ 100 H 30	100	300	497	1029.3 / 105	I1	85
5211100122061	HJ 150 H 15	150	150	317	1538.9 / 156.9	I1	76
5211100122062	HJ 150 H 30	150	300	502	1538.9 / 156.9	I1	128
5211100122071	HJ 200 H 15	200	150	327	2040.6 / 208.1	I1	121
5211100122072	HJ 200 H 30	200	300	507	2040.6 / 208.1	I1	186
5211100122084	HJ 300 H 15	300	150	382	2933 / 299.1	I1	240
5211100122083	HJ 300 H 30	300	300	547	2933 / 299.1	I1	360

Blueprint

