

HAC S Aluminium Hydraulic Cylinder

Product information



Holmatro aluminum cylinders (HAC) - Spring or hydraulic return

Unique specifications:

- Up to 50% lighter compared to steel cylinders - easy & ergonomic
- Duo power ring; a combination of a superior seal and an extremely strong composite bearing for a longer life span
- XL saddle optimally protects the plunger and guides the load as effectively as possible
- The plunger is coated with a hardened anodized layer, which makes it extremely wear & corrosion resistant

Standard supplied with:

- High flow female coupler A118
- Flat saddle
- Larger cylinders are equipped with handles for easy carrying and positioning

Also available:

- Tilting saddles
- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Код товара	Код	WLL ton	stroke length mm	Closed height mm	required oil cc	angle A2 °	Bec kg
5211100112267	HAC 20 S 5	20	50	164	141	-	2,6
5211100112265	HAC 20 S 10	20	100	214	283	-	3,2
5211100112261	HAC 20 S 15	20	150	264	424	-	3,9
5211100112269	HAC 30 S 5	30	50	182	221	-	4,7
5211100112268	HAC 30 S 10	30	100	232	442	40	5,9
5211100112262	HAC 30 S 15	30	150	282	663	40	7
5211100112271	HAC 50 S 5	50	50	183	354	-	6,9
5211100112270	HAC 50 S 10	50	100	233	709	40	8,3
5211100112263	HAC 50 S 15	50	150	283	1 063	40	9,8
5211100112273	HAC 100 S 5	100	50	225	716	40	17,8
5211100112272	HAC 100 S 10	100	100	275	1 431	40	20,9
5211100112264	HAC 100 S 15	100	150	325	2 147	40	24,1

Blueprint

