



HSC S Short Stroke Hydraulic Cylinder

Product information

Holmatro Short stroke cylinders (HSC) - Spring return

Unique specifications:

- Compact version, efficient in case of limited insertion space
- Stroke of 50mm on all models

Standard supplied with:

- Dirt scraper ring
 - Protects against pollution
 - Increases the life span
- Superior seal for an excellent static and dynamic sealing
- Splined plunger, no saddle needed
- High flow female coupler A118

Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

| Код товара | Код | WLL ton | Stroke mm | Closed height mm | required oil cc | Capacity kN/t | angle A1 ° | angle A2 ° | Bec kg |
|---------------|-------------|---------|-----------|------------------|-----------------|----------------|------------|------------|--------|
| 5211100112300 | HSC 10 S 5 | 10 | 50 | 100 | 69,3 | 99.8 / 10.2 | 5 | - | 2,9 |
| 5211100112301 | HSC 20 S 5 | 20 | 50 | 103 | 141,4 | 203.6 / 20.8 | 5 | - | 5,5 |
| 5211100112302 | HSC 30 S 5 | 30 | 50 | 106 | 221 | 318.1 / 32.4 | - | - | 6,1 |
| 5211100112303 | HSC 50 S 5 | 50 | 50 | 117 | 354 | 510.4 / 52 | - | - | 9,7 |
| 5211100112304 | HSC 100 S 5 | 100 | 50 | 141 | 716 | 1030.6 / 105.1 | - | 40 | 22,2 |

Blueprint

