



Stainless Steel Hand Winch MR500-5000

Product information



This stainless steel hand winch is corrosion resistant and is made of stainless steel 316. The worm gear winch is IP54 classified which means that it is resistant to splashing water and dust on the inside. This makes the winch resistant to the toughest conditions and has a very high corrosion resistance rating.

- winch suitable for lifting and pulling in compliance with EN13157
- static safety factor 4
- load pressure brake with double ratchet system for safe stable hold of the load
- closed gearbox to protect against environmental influence – protection classification IP54
- cable outlet upwards, downwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- stainless steel 316 body, drum, crank and all outgoing parts
- corrosion resistant

Options:

- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for floor mounting (FM)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- ATEX certified zone 2 and 22 (EX)
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C

Marking: According to standard

Standard: EN 13157

Safety factor: 4:1

Код товара	WLL ton	Model	Rope Ø mm	Rope capacity m	Capacity top layer kg	Bec kg
5013000500000610	0,5	MR500 SST	6	78,2	224	16
5013001500000610	1,5	MR1500 SST	10	41,3	846	30
5013003000000610	3	MR3000 SST	14	68,7	1 667	104
5013005000000610	5	MR5000 SST	18	42,9	3 276	135

Blueprint

