



## Heavy Duty Air Chain Hoists Red Rooster TMH (37.500 & 45.000 kg)

### Product information

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market.

#### Standard features:

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

#### ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

#### Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

**Marking:** According to standard, CE-marked

**Standard:** EN 14492-2

Код товара	WLL ton	Type	Chain falls	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Lifting speed with max.load m/min	Lowering speed with max.load m/min	Lifting speed without load m/min	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	Bec kg
5601TMH375TC3	37,5	Cord control	3	180	108	0,9	2	1,8	1 440	150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1 300
5601TMH375TP3E	37,5	Pendant control	3	180	108	0,9	2	1,8	1 440	150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1 300
5601TMH45TC3	45	Cord control	3	167	108	0,65	1,8	1,8	1 440	150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1 300
5601TMH45TP3E	45	Pendant control	3	167	108	0,65	1,8	1,8	1 440	150	557,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1 300

## Blueprint

