



Eye / Eye Crosby HG-226

Product information

End fittings are quenched and tempered, bodies heat treated by normalizing.

Turnbuckle eyes are forged elongated, by design, to maximize easy attachment in system and minimize stress in the eye. For turnbuckle sizes 6 mm through 64 mm, a shackle one size smaller can be reeved through eye.

Standard: According to Federal Specifications FF-T-791b.

Safety factor: 5:1

| Код товара | WLL ton | Thread dia. & take up mm | Thread dia. & take up inch | A mm | J open | K closed | M open | N closed | R mm | S mm | X closed | BB mm | Bec kg |
|--------------|---------|--------------------------|----------------------------|------|--------|----------|--------|----------|------|------|----------|-------|--------|
| 422100230100 | 0,23 | 6.35 x 102 | 1/4 x 4 | 6,35 | 303 | 202 | 314 | 213 | 20,6 | 8,64 | 44,6 | 103 | 0,13 |
| 422100360100 | 0,36 | 7.94 x 114 | 5/16 x 4-1/2 | 7,94 | 354 | 239 | 368 | 253 | 24,1 | 11,2 | 55,8 | 116 | 0,22 |
| 422100540100 | 0,54 | 9.53 x 152 | 3/8 x 6 | 9,53 | 446 | 294 | 463 | 311 | 28,7 | 13,5 | 62,9 | 155 | 0,34 |
| 422100100100 | 1 | 12.7 x 152 | 1/2 x 6 | 12,7 | 506 | 354 | 529 | 376 | 35,8 | 18 | 90,4 | 153 | 0,78 |
| 422100100105 | 1 | 12.7 x 305 | 1/2 x 12 | 12,7 | 819 | 514 | 841 | 536 | 35,8 | 18 | 89,9 | 314 | 1,19 |
| 422100160100 | 1,59 | 15.9 x 152 | 5/8 x 6 | 15,9 | 552 | 399 | 577 | 425 | 45,7 | 22,4 | 110 | 153 | 1,25 |
| 422100160105 | 1,59 | 15.9 x 305 | 5/8 x 12 | 15,9 | 865 | 560 | 891 | 586 | 45,7 | 22,4 | 110 | 315 | 1,87 |
| 422100240100 | 2,36 | 19.1 x 152 | 3/4 x 6 | 19,1 | 590 | 438 | 622 | 470 | 53,1 | 25,4 | 130 | 156 | 1,91 |

| | | | | | | | | | | | | | |
|--------------|------|------------|------------|------|-------|-------|-------|-------|------|------|-----|-----|------|
| 422100240105 | 2,36 | 19.1 x 305 | 3/4 x 12 | 19,1 | 905 | 600 | 937 | 632 | 53,1 | 25,4 | 129 | 320 | 2,78 |
| 422100240106 | 2,36 | 19.1 x 457 | 3/4 x 18 | 19,1 | 1 210 | 753 | 1 242 | 785 | 53,1 | 25,4 | 130 | 471 | 3,55 |
| 422100330100 | 3,27 | 22.2 x 305 | 7/8 x 12 | 22,2 | 932 | 627 | 970 | 665 | 60,5 | 31,8 | 147 | 309 | 4,01 |
| 422100330105 | 3,27 | 22.2 x 457 | 7/8 x 18 | 22,2 | 1 249 | 792 | 1 287 | 830 | 60,5 | 31,8 | 147 | 473 | 5,22 |
| 422100450107 | 4,54 | 25.4 x 152 | 1 x 6 | 25,4 | 666 | 514 | 711 | 559 | 76,2 | 36,3 | 165 | 157 | 4,36 |
| 422100450105 | 4,54 | 25.4 x 305 | 1 x 12 | 25,4 | 971 | 666 | 1 016 | 711 | 76,2 | 36,3 | 165 | 309 | 5,88 |
| 422100450106 | 4,54 | 25.4 x 457 | 1 x 18 | 25,4 | 1 276 | 819 | 1 321 | 864 | 76,2 | 36,3 | 165 | 462 | 7,4 |
| 422100450100 | 4,54 | 25.4 x 610 | 1 x 24 | 25,4 | 1 596 | 987 | 1 641 | 1 031 | 76,2 | 36,3 | 154 | 631 | 9,14 |
| 422100690100 | 6,89 | 31.8 x 305 | 1-1/4 x 12 | 31,8 | 1 070 | 766 | 1 127 | 822 | 91,2 | 46,2 | 216 | 306 | 9,01 |
| 422100690105 | 6,89 | 31.8 x 457 | 1-1/4 x 18 | 31,8 | 1 375 | 918 | 1 432 | 975 | 92,1 | 46,2 | 216 | 459 | 10,8 |
| 422100690106 | 6,89 | 31.8 x 610 | 1-1/4 x 24 | 31,8 | 1 694 | 1 085 | 1 751 | 1 141 | 91,2 | 46,2 | 216 | 625 | 12,6 |
| 422100970100 | 9,71 | 38.1 x 305 | 1-1/2 x 12 | 38,1 | 1 124 | 819 | 1 187 | 882 | 104 | 53,8 | 240 | 313 | 13 |
| 422100970105 | 9,71 | 38.1 x 457 | 1-1/2 x 18 | 38,1 | 1 428 | 971 | 1 492 | 1 035 | 104 | 53,8 | 240 | 465 | 15,4 |
| 422100970106 | 9,71 | 38.1 x 610 | 1-1/2 x 24 | 38,1 | 1 749 | 1 139 | 1 813 | 1 203 | 104 | 53,8 | 240 | 633 | 17,9 |
| 422101270100 | 12,7 | 44.5 x 457 | 1-3/4 x 18 | 44,5 | 1 457 | 1 000 | 1 534 | 1 076 | 118 | 60,5 | 253 | 467 | 23 |
| 422101270105 | 12,7 | 44.5 x 610 | 1-3/4 x 24 | 44,5 | 1 762 | 1 153 | 1 838 | 1 229 | 118 | 60,5 | 253 | 619 | 26,4 |
| 422101680100 | 16,8 | 50.8 x 610 | 2 x 24 | 50,8 | 1 922 | 1 313 | 2 011 | 1 402 | 148 | 68,3 | 331 | 622 | 37,9 |
| 422102720100 | 27,2 | 63.5 x 610 | 2-1/2 x 24 | 63,5 | 2 011 | 1 402 | 2 113 | 1 503 | 165 | 79,2 | 350 | 625 | 67,4 |
| 422103400100 | 34 | 69.9 x 610 | 2-3/4 x 24 | 69,9 | 2 066 | 1 456 | 2 180 | 1 571 | 178 | 82,6 | 383 | 626 | 79,1 |

Blueprint

