

## Push Trolley POWERTEX PPT-S2



### Product information

**POWERTEX**



POWERTEX PPT-S2 is a high quality, durable low built push trolley that is easy to install on horizontal beams and rails.

The trolleys can be used for I-beams with plane flanges (such as IPE, HEA or HEB types) or beams with sloping flanges (such as INP-beams).

The trolley can easily be positioned along the beam by pushing or pulling thanks to high quality steel wheels with bearings.

#### Features:

- Safe - All POWERTEX trolleys are proof load tested 1,5 x WLL
- **Mechanical stops integrated in the design** to prevent derailing
- Equipped with connection plate with eye to hoist's upper hook or direct connection
- Connection plate can be turned 90 degrees to allow direct connection to POWERTEX S2 hoists without need of intermediate hook/eye
- Rubber bumpers to absorb shock loads on impact to rail ending
- Equipped with RFID for quick registration and maintenance
- Marked with QR code to allow access to user manuals at any time
- PPT-S2 is easy to mount and dismount on a horizontal rail or beam
- The 3 piece design makes installation quick and ergonomically
- The shaft is easily locked using the lock plate (No need to use large castle nut nor collar pins)
- Wheel shafts are robotic welded for high quality weld seams
- Large steel wheels equipped with double sided sealed bearings that do not need maintenance
- Powder painted side panels gives a nice lasting finish
- Fits most types of beam profiles and most brands of lifting blocks and electric hoists
- Longer shafts for wider beams can be supplied from stock in EU
- Can be turned into Blackline version BT by adding the included grey label over the shiny nameplate.

Blackline BT products are suitable to be used in theatres and entertainment industry.

**Marking:** According to standard, CE-marked

**Standard:** EN 13157

**Safety factor:** 4:1

Код товара	WLL ton	Beam width mm	Model	Minimum radius mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	S mm	Bec kg
502500031520210	0,25	50-152	PPT-S2	800	188	208	137	50	29	1 – 1,5	28	6	104	27	4,6
502500051350210	0,5	50-135	PPT-S2	800	205	198	150	55	30	1,5 – 2	28	8	111	27	6,8
502500052150210	0,5	130-215	PPT-S2	800	205	278	150	55	30	1,5 - 2	28	8	111	27	7,6
502500053000210	0,5	215-300	PPT-S2	800	205	363	150	55	30	1,5 – 2	28	8	111	27	8,4
502500101400210	1	55-140	PPT-S2	1 000	242	211	174	68	30	1,5 – 2	32	10	118	28	11,2
502500102150210	1	140-215	PPT-S2	1 000	242	286	174	68	30	1,5 – 2	32	10	118	28	12,2
502500103000210	1	215-300	PPT-S2	1 000	242	371	174	68	30	1,5 – 2	32	10	118	28	13,5
502500201550210	2	65-155	PPT-S2	1 100	270	238	194	80	49	1,5 – 2	40	12	147	27	16,9
502500202300210	2	150-230	PPT-S2	1 100	270	313	194	80	49	1,5 – 2	40	12	147	27	18,1
502500203000210	2	230-300	PPT-S2	1 100	270	383	194	80	49	1,5 – 2	40	12	147	27	19,3
502500301600210	3	90-160	PPT-S2	1 300	325	246	234	100	60	2 – 3	49	14	177	29	28,6
502500302300210	3	160-230	PPT-S2	1 300	325	316	234	100	60	2 – 3	49	14	177	29	30,2
502500303000210	3	230-300	PPT-S2	1 300	325	386	234	100	60	2 – 3	49	14	177	29	31,8
502500501800210	5	90-180	PPT-S2	1 500	370	280	267	110	79	2 – 3	59	16	219	29	44,8
502500502300210	5	180-230	PPT-S2	1 500	370	330	267	110	79	2 – 3	59	16	219	29	46,5
502500503000210	5	230-300	PPT-S2	1 500	370	330	267	110	79	2 – 3	59	16	219	29	48,9

# Blueprint

