



Master Link Assembly X-006

Product information

- Welded Master Link designed for 3-4 legs Chain, Wire Rope and Webbing Slings.
- The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.
- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Manufactured in accordance with EN 1677- 4 and ASME B30.26.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Marking: According to standard, CE-marked

Standard: EN 1677-4

Safety factor: 4:1

Класс: 10

Код товара	Код	WLL ton	EWL ton	Proof Load kN	For chain gr 10 Ø 3-4 leg mm	Can be used up to single hook acc. to DIN 15401 no.	WLL β 0-45° ton	D mm	A mm	B mm	d mm	a mm	b mm	Bec kg
402100420410	BD-19 + 2 DD+13	4,2	189	103	6	5	4,2	19	135	75	13	54	25	1,3
402100820410	BD-22 + 2 DD+16	8,2	230	201	7,8	6	8,2	22	160	90	16	70	34	2,2
402101070410	BD-28 + 2 DD+19	10,7	265	262	10	8	10,7	28	180	100	19	85	40	3,9
402101570410	BD-32 + 2 DD+22	15,7	315	385	13	10	15,7	32	200	110	22	115	50	6,1
402102220410	BD-36 + 2 DD+28	22,2	325	544	16	16	22,2	36	260	140	28	140	65	10,6
402103410410	BD-50 + 2 DD+32	34,1	450	835	20	32	34,1	50	300	200	32	150	70	21,2
402104000410	BD-50 + 2 DD+36	40	470	980	22	32	40,0	50	300	200	36	170	75	23,8

Blueprint

