



Steel Wire Rope ROPETEX S19 Stainless Steel

Product information

ROPETEX



ROPETEX S19 is a stainless steel wire rope. It's very corrosion resistant and durable, well suited for marine applications. The S19 rope has very little stretch which makes it excellent for standing rigging, stays, controls and architectural balustrades and green walls.

ROPETEX S19 can be provided with swaged terminals as end fittings.

Marking: According to standard

Standard: EN 12385-10
except material

Fill factor: 0,74

Stay rope



Agriculture and livestock



Код товара	Rope Diameter,	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Bec kg/100m
108100101620018	1	1 570	Stainless	S	0,83	0,58	No-Lube	0,49
108100102620018	1	1 570	Stainless	Z	0,83	0,58	No-Lube	0,49
108100131620018	1,25	1 570	Stainless	S	1,29	0,91	No-Lube	0,74
108100132620018	1,25	1 570	Stainless	Z	1,29	0,91	No-Lube	0,74

108100151620018	1,5	1 570	Stainless	S	1,86	1,31	No-Lube	1,09
108100152620018	1,5	1 570	Stainless	Z	1,86	1,31	No-Lube	1,09
108100201620018	2	1 570	Stainless	S	3,3	2,33	No-Lube	1,94
108100202620018	2	1 570	Stainless	Z	3,3	2,33	No-Lube	1,94
108100251620018	2,5	1 570	Stainless	S	5,16	3,65	No-Lube	3,03
108100252620018	2,5	1 570	Stainless	Z	5,16	3,65	No-Lube	3,03
108100301620018	3	1 570	Stainless	S	7,43	5,25	No-Lube	4,37
108100302620018	3	1 570	Stainless	Z	7,43	5,25	No-Lube	4,37
108100401620018	4	1 570	Stainless	S	13,2	9,34	No-Lube	7,76
108100402620018	4	1 570	Stainless	Z	13,2	9,34	No-Lube	7,76
108100501620018	5	1 570	Stainless	S	20,6	14,6	No-Lube	12,1
108100502620018	5	1 570	Stainless	Z	20,6	14,6	No-Lube	12,1
108100601620018	6	1 570	Stainless	S	29,7	21	No-Lube	17,5
108100602620018	6	1 570	Stainless	Z	29,7	21	No-Lube	17,5
108100701620018	7	1 570	Stainless	S	40,5	28,6	No-Lube	23,8
108100702620018	7	1 570	Stainless	Z	40,5	28,6	No-Lube	23,8
108100801620018	8	1 570	Stainless	S	52,8	37,4	No-Lube	31
108101001620018	10	1 570	Stainless	S	82,6	58,4	No-Lube	48,5