

Steel Wire Rope ROPETEX S65 Stainless Steel

Product information

ROPETEX



ROPETEX S65 is a stainless steel rope, the most commonly used range is from 8 to 38 mm. It can be used for cranes, hoists, slings and a wide range of various other applications.

ROPETEX S65 is equipped with an Independent Wire Rope Core (IWRC) which gives it a high breaking strength and dimensionally stability, especially when used on sheaves or drums.

In stainless steel (AISI 316) it's well suited for marine and aggressive environments.

Marking: According to standard

Standard: EN 12385-4
except material

Fill factor: 0,59

General use




Winch rope



Stay rope



Overhead cranes



Agriculture and livestock



Slings



Код товара	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force, kN	Finish	Rope lay.	Bec kg/100m
108101004620048	10	1 570	46	56	Stainless	sZ	40,9
108101204620048	12	1 570	66,2	80,5	Stainless	sZ	58,9
108101404620048	14	1 570	90,2	110	Stainless	sZ	80,2
108101604620048	16	1 570	118	143	Stainless	sZ	105
108101804620048	18	1 570	149	181	Stainless	sZ	133
108102004620048	20	1 570	184	224	Stainless	sZ	164
108102204620048	22	1 570	249,7	270	Stainless	sZ	198
108102404620048	24	1 570	265	322	Stainless	sZ	236