



Steel Wire Rope ROPETEX S33 PVC

Product information

ROPETEX



ROPETEX S33 is a galvanized rope equipped with a Wire Strand Core (WSC) and has a black PVC coating. It can be a good choice for basic lifting applications such as lifting slings, security rope in studios/theaters premises, etc. It's most used in small diameters up to 8 mm. Ropetex S33 is equipped with a steel core, which gives the rope less flexible than S14 PVC but has higher strength.

The PVC coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

Marking: According to standard

Standard: EN 12385-4
except from coating

Fill factor: 0,53

General use



Slings



| Код товара | Rope Diameter, mm | Inner diameter mm | Tensile strength N/mm ² | Steel area mm ² | Min. Breaking force, kN | Цвет | Finish | Rope lay. | Bec kg/100m |
|-----------------|-------------------|-------------------|------------------------------------|----------------------------|-------------------------|-------|------------|-----------|-------------|
| 105130040030034 | 4 | 3 | 1 770 | 3,76 | 5,77 | Black | Galvanized | sZ | 4,2 |
| 105130080060034 | 8 | 6 | 1 770 | 15 | 23,1 | Black | Galvanized | sZ | 16,1 |