

Fast Connector Socket FCS - with bolt

Product information

Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Can be used to terminate all constructions of wire rope including high performance ropes, anti-rotation ropes and standard 6 strand ropes.

The connector has to be moulded/casted on the steel wire rope with wirelock resin.



Код товара	Код	Rope Ø range mm	MBL	Finish	TB mm	TL mm	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	Bec kg
122101300155	FCS 701 B	11-13	20	Painted	80	150	62	61	27	15	25	12	25	50	33	49	46	1,6
122101300152	FCS 701 B.G	11-13	20	Galvanized	80	150	62	61	27	15	25	12	25	50	33	49	46	1,6
122101600155	FCS 702 B	13-16	25	Painted	96	182	72	78	32	18	30	14	32	58	38	60	59	2,6
122101600152	FCS 702 B.G	13-16	25	Galvanized	96	182	72	78	32	18	30	14	32	58	38	60	59	2,6
122101900155	FCS 703 B	16-19	40	Painted	107	218	85	93	40	21	35	16	38	70	45	70	69	4,5
122101900152	FCS 703 B.G	16-19	40	Galvanized	107	218	85	93	40	21	35	16	38	70	45	70	69	4,5
122102200155	FCS 704 B	20-22	55	Painted	123	253	102	106	45	24	41	19	44	80	50	82	81	6,5
122102200152	FCS 704 B.G	20-22	55	Galvanized	123	253	102	106	45	24	41	19	44	80	50	82	81	6,5
122102600155	FCS 705 B	23-26	75	Painted	138	298	115	123	60	28	51	22	51	104	60	95	90	11
122102600152	FCS 705 B.G	23-26	75	Galvanized	138	298	115	123	60	28	51	22	51	104	60	95	90	11
122102900155	FCS 706 B	27-29	90	Painted	160	357	140	152	65	32	57	25	57	114	70	107	116	16
122102900152	FCS 706 B.G	27-29	90	Galvanized	160	357	140	152	65	32	57	25	57	114	70	107	116	16

Blueprint

