



Standard Reeve Crane Blocks 1 Sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Код товара	WLL	Model	For wire Ø mm	Hook size	Bec kg
6097SRB225141125E	12,5	SRB 225 .14 .1 .12,5 .E	14	5	75
6097SRB260141125E	12,5	SRB 260 .14 .1 .12,5 .E	14	5	110
6097SRB260161125E	12,5	SRB 260 .16 .1 .12,5 .E	16	5	110
6097SRB22514116E	16	SRB 225 .14 .1 .16 .E	14	5	100

6097SRB26016116E	16	SRB 260 .16 .1 .16 .E	16	5	110
6097SRB28516116E	16	SRB 285 .16 .1 .16 .E	16	6	160
6097SRB32016116E	16	SRB 320 .16 .1 .16 .E	16	6	160
6097SRB32019116E	16	SRB 320 .19 .1 .16 .E	19	6	160
6097SRB35516116EA	16	SRB 355 .16 .1 .16 .E .A	16	6	180
6097SRB35519116E	16	SRB 355 .19 .1 .16 .E	19	6	180
6097SRB35519120E	20	SRB 355 .19 .1 .20 .E	19	10	225
6097SRB40022129E	29	SRB 400 .22 .1 .29 .E	22	8	290
6097SRB45024132EA	32	SRB 450 .24 .1 .32 .E .A	24	10	455
6097SRB45026132EA	32	SRB 450 .26 .1 .32 .E .A	26	10	455
6097SRB45024132EB	32	SRB 450 .24 .1 .32 .E .B	24	10	590
6097SRB45026132EB	32	SRB 450 .26 .1 .32 .E .B	26	10	590
6097SRB45024140EB	40	SRB 450 .24 .1 .40 .E .B	24	12	590
6097SRB45026140E	40	SRB 450 .26 .1 .40 .E	26	12	590
6097SRB52824150E	50	SRB 528 .24 .1 .50 .E	24	16	725
6097SRB52826150E	50	SRB 528 .26 .1 .50 .E	26	16	725
6097SRB52828150E	50	SRB 528 .28 .1 .50 .E	28	16	725
6097SRB57528150E	50	SRB 575 .28 .1 .50 .E	28	16	930
6097SRB63032163E	63	SRB 630 .32 .1 .63 .E	32	16	1 000
6097SRB67028163E	63	SRB 670 .28 .1 .63 .E	28	16	1 800
6097SRB67032163E	63	SRB 670 .32 .1 .63 .E	32	16	1 800

Blueprint

