



Standard Reeve Crane Blocks 1 Sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

| Код товара | WLL ton | Model no. | For wire Ø mm | Hook size | Ø D1 mm | Ø D2 mm | B mm | O mm | TA mm | TB mm | TL mm | L mm | T mm | Ø Z mm | Bec kg |
|-------------------|---------|-------------------------|---------------|-----------|---------|---------|------|------|-------|-------|-------|------|------|--------|--------|
| 6097SRB225141125E | 12,5 | SRB 225 .14 .1 .12,5 .E | 14 | 5 | 260 | 225 | 523 | 55 | 345 | 170 | 798 | 913 | 28 | 32 | 75 |
| 6097SRB260141125E | 12,5 | SRB 260 .14 .1 .12,5 .E | 14 | 5 | 300 | 260 | 548 | 55 | 400 | 185 | 833 | 948 | 28 | 32 | 110 |
| 6097SRB260161125E | 12,5 | SRB 260 .16 .1 .12,5 .E | 16 | 5 | 300 | 260 | 548 | 55 | 400 | 185 | 833 | 948 | 28 | 32 | 110 |
| 6097SRB22514116E | 16 | SRB 225 .14 .1 .16 .E | 14 | 5 | 260 | 225 | 548 | 55 | 345 | 180 | 823 | 938 | 28 | 32 | 100 |

| | | | | | | | | | | | | | | | |
|-------------------|----|--------------------------|----|----|-----|-----|-------|----|-----|-----|-------|-------|----|----|-------|
| 6097SRB26016116E | 16 | SRB 260 .16 .1 .16 .E | 16 | 5 | 300 | 260 | 548 | 55 | 400 | 185 | 833 | 948 | 28 | 32 | 110 |
| 6097SRB28516116E | 16 | SRB 285 .16 .1 .16 .E | 16 | 6 | 320 | 280 | 608 | 57 | 420 | 165 | 908 | 1 033 | 28 | 32 | 160 |
| 6097SRB32016116E | 16 | SRB 320 .16 .1 .16 .E | 16 | 6 | 365 | 320 | 628 | 59 | 450 | 205 | 951 | 1 076 | 28 | 32 | 160 |
| 6097SRB32019116E | 16 | SRB 320 .19 .1 .16 .E | 19 | 6 | 365 | 320 | 628 | 59 | 450 | 205 | 951 | 1 081 | 35 | 37 | 160 |
| 6097SRB35516116EA | 16 | SRB 355 .16 .1 .16 .E .A | 16 | 6 | 410 | 355 | 668 | 59 | 500 | 195 | 1 013 | 1 138 | 28 | 32 | 180 |
| 6097SRB35519116E | 16 | SRB 355 .19 .1 .16 .E | 19 | 6 | 410 | 355 | 668 | 59 | 500 | 195 | 1 013 | 1 138 | 28 | 32 | 180 |
| 6097SRB35519120E | 20 | SRB 355 .19 .1 .20 .E | 19 | 10 | 410 | 355 | 713 | 76 | 500 | 225 | 1 053 | 1 204 | 35 | 37 | 225 |
| 6097SRB40022129E | 29 | SRB 400 .22 .1 .29 .E | 22 | 8 | 460 | 400 | 743 | 69 | 570 | 240 | 1 128 | 1 273 | 40 | 43 | 290 |
| 6097SRB45024132EA | 32 | SRB 450 .24 .1 .32 .E .A | 24 | 10 | 515 | 450 | 833 | 76 | 600 | 350 | 1 256 | 1 422 | 45 | 52 | 455 |
| 6097SRB45026132EA | 32 | SRB 450 .26 .1 .32 .E .A | 26 | 10 | 515 | 450 | 833 | 76 | 600 | 350 | 1 256 | 1 422 | 45 | 52 | 455 |
| 6097SRB45024132EB | 32 | SRB 450 .24 .1 .32 .E .B | 24 | 10 | 515 | 450 | 833 | 76 | 600 | 410 | 1 256 | 1 422 | 45 | 52 | 590 |
| 6097SRB45026132EB | 32 | SRB 450 .26 .1 .32 .E .B | 26 | 10 | 515 | 450 | 833 | 76 | 600 | 410 | 1 256 | 1 422 | 45 | 52 | 590 |
| 6097SRB45024140EB | 40 | SRB 450 .24 .1 .40 .E .B | 24 | 12 | 515 | 450 | 1 074 | 84 | 600 | 410 | 1 487 | 1 665 | 45 | 52 | 590 |
| 6097SRB45026140E | 40 | SRB 450 .26 .1 .40 .E | 26 | 12 | 515 | 450 | 918 | 84 | 605 | 323 | 1 338 | 1 516 | 45 | 52 | 590 |
| 6097SRB52824150E | 50 | SRB 528 .24 .1 .50 .E | 24 | 16 | 596 | 528 | 934 | 97 | 710 | 353 | 1 412 | 1 604 | 45 | 52 | 725 |
| 6097SRB52826150E | 50 | SRB 528 .26 .1 .50 .E | 26 | 16 | 596 | 528 | 934 | 97 | 710 | 353 | 1 412 | 1 604 | 45 | 52 | 725 |
| 6097SRB52828150E | 50 | SRB 528 .28 .1 .50 .E | 28 | 16 | 595 | 528 | 934 | 97 | 710 | 353 | 1 412 | 1 614 | 50 | 59 | 725 |
| 6097SRB57528150E | 50 | SRB 575 .28 .1 .50 .E | 28 | 16 | 650 | 575 | 958 | 97 | 770 | 333 | 1 459 | 1 661 | 50 | 59 | 930 |
| 6097SRB63032163E | 63 | SRB 630 .32 .1 .63 .E | 32 | 16 | 720 | 630 | 985 | 97 | 825 | 353 | 1 521 | 1 728 | 60 | 66 | 1 000 |
| 6097SRB67028163E | 63 | SRB 670 .28 .1 .63 .E | 28 | 16 | 760 | 670 | 1 173 | 97 | 870 | 473 | 1 738 | 1 940 | 50 | 59 | 1 800 |
| 6097SRB67032163E | 63 | SRB 670 .32 .1 .63 .E | 32 | 16 | 760 | 670 | 1 173 | 97 | 870 | 473 | 1 738 | 1 945 | 60 | 66 | 1 800 |

Blueprint

