



Standard Reeve Crane Blocks 3 Sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

| Код товара | WLL ton | Model no. | For wire Ø mm | Hooksize | Ø D1 mm | Ø D2 mm | B mm | O mm | TA mm | TB mm | TL mm | L mm | T mm | Ø Z mm | Bec kg |
|-------------------|---------|------------------------|---------------|----------|---------|---------|-------|------|-------|-------|-------|-------|------|--------|--------|
| 6097SRB26014325E | 25 | SRB 260 .14 .3 .25 .E | 14 | 8 | 300 | 260 | 658 | 69 | 400 | 260 | 953 | 1 088 | 28 | 32 | 210 |
| 6097SRB26016325E | 25 | SRB 260 .16 .3 .25 .E | 16 | 8 | 300 | 260 | 658 | 69 | 400 | 260 | 953 | 1 088 | 28 | 32 | 210 |
| 6097SRB28516329E | 29 | SRB 285 .16 .3 .29 .E | 16 | 8 | 325 | 285 | 668 | 69 | 400 | 270 | 978 | 1 113 | 28 | 32 | 210 |
| 6097SRB32016329E | 29 | SRB 320 .16 .3 .29 .E | 16 | 8 | 365 | 320 | 713 | 69 | 450 | 240 | 1 048 | 1 183 | 28 | 32 | 225 |
| 6097SRB35519332E | 32 | SRB 355 .19 .3 .32 .E | 19 | 10 | 410 | 355 | 753 | 76 | 500 | 262 | 1 093 | 1 244 | 35 | 37 | 325 |
| 6097SRB36019340E | 40 | SRB 360 .19 .3 .40 .E | 19 | 12 | 410 | 360 | 839 | 84 | 500 | 362 | 1 179 | 1 342 | 35 | 37 | 455 |
| 6097SRB40022340E | 40 | SRB 400 .22 .3 .40 .E | 22 | 12 | 460 | 400 | 864 | 84 | 570 | 353 | 1 244 | 1 412 | 40 | 43 | 500 |
| 6097SRB40022350E | 50 | SRB 400 .22 .3 .50 .E | 22 | 16 | 460 | 400 | 864 | 97 | 570 | 353 | 1 244 | 1 426 | 40 | 43 | 500 |
| 6097SRB40022350E | 50 | SRB 400 .22 .3 .50 .E | 22 | 16 | 460 | 400 | 864 | 97 | 570 | 373 | 1 244 | 1 426 | 40 | 43 | 540 |
| 6097SRB45022363E | 63 | SRB 450 .22 .3 .63 .E | 22 | 16 | 515 | 450 | 963 | 97 | 600 | 343 | 1 376 | 1 558 | 40 | 43 | 680 |
| 6097SRB45024363E | 63 | SRB 450 .24 .3 .63 .E | 24 | 16 | 515 | 450 | 963 | 97 | 600 | 383 | 1 376 | 1 568 | 45 | 52 | 770 |
| 6097SRB45026363E | 63 | SRB 450 .26 .3 .63 .E | 26 | 16 | 515 | 450 | 963 | 97 | 600 | 383 | 1 376 | 1 568 | 45 | 52 | 770 |
| 6097SRB52826380E | 80 | SRB 528 .26 .3 .80 .E | 24 | 20 | 595 | 528 | 1 132 | 110 | 710 | 462 | 1 612 | 1 822 | 45 | 52 | 1 270 |
| 6097SRB52826380E | 80 | SRB 528 .26 .3 .80 .E | 26 | 20 | 595 | 528 | 1 132 | 110 | 710 | 462 | 1 612 | 1 822 | 45 | 52 | 1 270 |
| 6097SRB528263100E | 100 | SRB 528 .26 .3 .100 .E | 26 | 25 | 595 | 528 | 1 223 | 132 | 710 | 462 | 1 683 | 1 913 | 45 | 52 | 1 270 |
| 6097SRB528283100E | 100 | SRB 528 .28 .3 .100 .E | 28 | 25 | 595 | 528 | 1 223 | 132 | 710 | 462 | 1 683 | 1 923 | 50 | 59 | 1 270 |
| 6097SRB670283125E | 125 | SRB 670 .28 .3 .125 .E | 28 | 25 | 760 | 670 | 1 353 | 132 | 870 | 642 | 1 918 | 2 158 | 50 | 59 | 2 900 |
| 6097SRB670323125E | 125 | SRB 670 .32 .3 .125 .E | 32 | 25 | 760 | 670 | 1 353 | 132 | 870 | 642 | 1 918 | 2 163 | 60 | 66 | 2 900 |

Blueprint

