



## Standard Reeve Crane Blocks 5 sheaves

### Product information

#### General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

#### Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

#### Important:

**Inquiries for custom versions are welcome!**

Код товара	WLL ton	Model	For wire Ø mm	Hooksize	Bec kg
6097SRB35516550E	50	SRB 355 .16 .5 .50 .E	16	16	500
6097SRB36019563E	63	SRB 360 .19 .5 .63 .E	19	16	600
6097SRB36019580E	80	SRB 360 .19 .5 .80 .E	19	20	820
6097SRB40019580E	80	SRB 400 .19 .5 .80 .E	19	20	835
6097SRB40022580E	80	SRB 400 .22 .5 .80 .E	22	20	835
6097SRB45022580E	80	SRB 450 .22 .5 .80 .E	22	20	1 025
6097SRB450245100E	100	SRB 450 .24 .5 .100 .E	24	25	1 120
6097SRB450265100E	100	SRB 450 .26 .5 .100 .E	26	25	1 120
6097SRB528245125E	125	SRB 528 .24 .5 .125 .E	24	32	1 820
6097SRB528265125E	125	SRB 528 .26 .5 .125 .E	26	32	1 820
6097SRB528285125E	125	SRB 528 .28 .5 .125 .E	26	32	1 850
6097SRB528285160E	160	SRB 528 .28 .5 .160 .E	28	40	1 820
6097SRB670285200E	200	SRB 670 .28 .5 .200 .E	28	50	3 560
6097SRB670325200E	200	SRB 670 .32 .5 .200 .E	32	50	3 560

# Blueprint

