



Latch hook with ball bearing swivel, grade 80

Product information

Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

Marking: According to standard, CE-marked

Standard: EN 1677-2

Safety factor: 4:1

Класс: 8

| Код товара | WLL ton | EWL mm | For chain dia. mm | A mm | B mm | E mm | M mm | L1 mm | L mm | N mm | C mm | H mm | Вес kg |
|--------------|------------|-----------|----------------------|---------|---------|---------|---------|----------|---------|---------|---------|---------|-----------|
| 420500110880 | 1,12 | - | 6 | 33 | 33 | 24 | 69 | 138 | 168 | 16 | 11 | 19 | 0,65 |
| 420500200880 | 2 | 170 | 8 | 45 | 36 | 28 | 88 | 170 | 208 | 20 | 13 | 23 | 0,95 |
| 420500320880 | 3,15 | 207 | 10 | 53 | 42 | 31 | 105 | 207 | 254 | 23 | 15 | 29 | 1,71 |
| 420500530880 | 5,3 | 248 | 13 | 64 | 50 | 40 | 135 | 248 | 305 | 32 | 17 | 38 | 3,13 |
| 420500800880 | 8 | 295 | 16 | 68 | 61 | 45 | 161 | 295 | 367 | 37 | 21 | 45 | 5,44 |
| 420501250880 | 12,5 | 356 | 20 | 90 | 74 | 56 | 194 | 356 | 434 | 49 | 25 | 50 | 9,5 |

Blueprint

