



STA-S Spread Anchor

Product information

Transport Anchor STA-S is suitable for loads from 0.7 up to 22.0 t and for use in both thin panels and plates. The head of the spread anchor has a hole in which the locking bolt of the lifting eye is mounted. Other holes in the anchor are for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

| Код товара | Load grp. | Длина мм | Finish | L mm | a mm | b mm | c mm | Hole mm | Вес kg |
|----------------|-----------|----------|-----------|---------|---------|---------|---------|---------|-----------|
| 65012202501501 | 2,5 | 150 | Untreated | 150 | 30 | 14 | 10 | 14x20 | 0,32 |
| 65012202501502 | 2,5 | 150 | HDG | 150 | 30 | 14 | 10 | 14x20 | 0,32 |
| 65012202502001 | 2,5 | 200 | Untreated | 200 | 30 | 14 | 10 | 14x20 | 0,42 |
| 65012205001801 | 5 | 180 | Untreated | 180 | 40 | 20 | 10 | 20x22 | 0,75 |
| 65012205001802 | 5 | 180 | HDG | 180 | 40 | 20 | 10 | 20x22 | 0,78 |
| 65012205002401 | 5 | 240 | Untreated | 240 | 40 | 20 | 10 | 20x22 | 1,01 |
| 65012205002402 | 5 | 240 | HDG | 240 | 40 | 20 | 10 | 20x22 | 1,05 |
| 65012207502601 | 7,5 | 260 | Untreated | 260 | 60 | 26 | 16 | 26x30 | 1,68 |
| 65012207502602 | 7,5 | 260 | HDG | 260 | 60 | 26 | 16 | 26x30 | 1,8 |

Blueprint

