



Starcon STA-SE one-sided anchor

Product information

The Starcon STA-SE is designed specifically to tilt panels from horizontal to vertical position in the direction where the notch is located. Unlike the STA-SA anchor, the STA-SE anchor can only handle loads in one direction, making it particularly suitable for thin elements or elements with limited space for the anchor location.

The anchor head has a hole for mounting the ring coupling locking bolt and additional holes for reinforcement located in the center of the anchor. This makes the STA-SE anchor ideal for tilting and turning prefabricated elements, as well as for erecting and mounting.

Areas of application: Concrete elements that need to be turned

Advantages: Multiple reinforcement placement options to ensure optimal lifting performance.

Flipping Elements

Quick connection/disconnection with shapes and Starcon ring coupling, perfect for efficient transport and setup.

Load group: 2.5t – 17t

Technical information: CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

EPD: Our Environmental Product Declarations (EPDs) are available in the LCA NO calculator/software. These EPDs have been prepared in strict accordance with ISO 14025 and EN 15804 standards.

Download the EPDs from the LCA database:

Untreated Products: [Starcon Lifting and Handling Systems for Concrete elements - Untreated - EPD Norge](#)

Surface treated Products: [Starcon Lifting and Handling Systems for Concrete elements - Surface Treated. - EPD Norge](#)

Marking: CE-marked

Blueprint

