



STA-Z 2-Hole Anchor

Product information

The 2-hole transport anchor STA-Z is suitable for loads from 0.7 up to 22.0 t. The STA-Z 2-hole anchor is almost similar to the transport anchor STA-S. The STA-Z 2-hole anchor, however, uses more reinforcement which is mounted through the lower hole. The head of the anchor has a hole in which the locking bolt of the ring clutch is mounted. Other holes in the anchor are meant for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

| Код товара | Load grp. | Длина мм | Finish | L мм | a мм | b мм | c мм | Hole mm | Вес kg |
|----------------|-----------|----------|-----------|------|------|------|------|---------|--------|
| 65012602500901 | 2,5 | 90 | Untreated | 90 | 30 | 14 | 10 | 14x20 | 0,16 |
| 65012602500902 | 2,5 | 90 | HDG | 90 | 30 | 14 | 10 | 14x20 | 0,17 |
| 65012605001201 | 5 | 120 | Untreated | 120 | 40 | 18 | 15 | 18x22 | 0,42 |
| 65012605001202 | 5 | 120 | HDG | 120 | 40 | 18 | 15 | 18x22 | 0,42 |
| 65012607501601 | 7,5 | 160 | Untreated | 160 | 60 | 26 | 16 | 26x30 | 0,91 |
| 65012607501602 | 7,5 | 160 | HDG | 160 | 60 | 26 | 16 | 26x30 | 0,92 |
| 65012610001701 | 10 | 170 | Untreated | 170 | 60 | 30 | 20 | 28x30 | 1,26 |
| 65012610001702 | 10 | 170 | HDG | 170 | 60 | 30 | 20 | 28x30 | 1,26 |

Blueprint

