

## **STA-Z 2-Hole Anchor**

## **Product information**

The 2-hole transport anchor STA-Z is suitable for loads from 0.7 up to 22.0 t. The STA-Z 2-hole anchor is almost similar to the transport anchor STA-S. The STA-Z 2-hole anchor, however, uses more reinforcement which is mounted through the lower hole. The head of the anchor has a hole in which the locking bolt of the ring clutch is mounted. Other holes in the anchor are meant for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Код товара	Load grp.	Длина мм	Finish	L mm	a mm	b mm	c mm	Hole mm	Bec kg
65012602500901	2,5	90	Untreated	90	30	14	10	14x20	0,16
65012602500902	2,5	90	HDG	90	30	14	10	14x20	0,17
65012605001201	5	120	Untreated	120	40	18	15	18x22	0,42
65012605001202	5	120	HDG	120	40	18	15	18x22	0,42
65012607501601	7,5	160	Untreated	160	60	26	16	26x30	0,91
65012607501602	7,5	160	HDG	160	60	26	16	26x30	0,92
65012610001701	10	170	Untreated	170	60	30	20	28x30	1,26
65012610001702	10	170	HDG	170	60	30	20	28x30	1,26

## Blueprint

