



## Eye Self Locking Hook X-025

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Marking:** According to standard

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Класс:** 10

Код товара	Chain diameter mm	WLL ton	EWL mm	A mm	D mm	H mm	K mm	P mm	T mm	Вес kg
402300140720	6	1,4	110	21	10	19	110	28	15	0,5
402300250720	7-8	2,5	136	25	11	24	136	34	20	0,8
402300400720	10	4	167	32	13	30	167	44	26	1,5
402300670720	13	6,7	207	40	16	39	207	51	30	3
402301000720	16	10	252	50	21	49	252	60	36	5,8
402301600720	20	16	290	60	23	65	290	70	53	10
402301900720	22	19	319	70	24	63	319	80	49	12,5
402302650720	26	26,5	343	80	25	69	343	99	56	15

# Blueprint

