



Welded Master Link Assembly X-0082

Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Marking: According to standard, CE-marked

Standard: EN 1677-4

Safety factor: 4:1

Класс: 10

Код товара	Код	WLL ton	EWL mm	Proof Load kN	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 3-4 leg mm	WLL 0°-45° τ	Used to single hook acc. to DIN 15401 No.	D mm	A mm	B mm	d mm	a mm	b mm	Bec kg
402100360440	ED-22	3,55	394	87	6,7,8	6	3,55	25	22	340	180	13	54	25	3,2
402100560440	ED-28	5,6	374	137	10	7,8	5,6	25	28	340	180	16	70	34	5,4
402100950440	ED-32	9,5	425	233	13	10	9,5	25	32	340	180	19	85	40	7,4
402101410440	ED-40	14,1	455	343	16	13	14,1	25	40	340	180	22	115	50	12,1
402102110440	ED-40	21,2	480	519	20	16	21,2	25	40	340	180	25	140	65	14,2

Blueprint

