



Welded Master Link Assembly X-006L

Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured

Marking: According to standard, CE-marked

Standard: EN 1677-4

Safety factor: 4:1

Класс: 10

Код товара	Код	WLL ton	EWL mm	Proof Load kN	For chain gr 10 Ø 3-4 leg mm	WLL 0°-45° τ	Used to single hook acc. to DIN 15401 No.	A mm	B mm	D mm	a mm	b mm	d mm	Вес kg
402100420450	BD-19 + 2 DD+13	4,2	245	103	6	4,2	5	135	75	19	110	60	13	1,6
402100820450	BD-22 + 2 DD+16	8,2	270	201	7,8	8,2	6	160	90	22	110	60	16	2,5
402101070450	BD-32 + 2 DD+22	10,7	360	262	10	10,7	10	200	110	32	160	90	22	6,9
402101570450	BD-36 + 2 DD+28	15,7	440	385	13	15,7	16	260	140	36	180	100	28	11,8
402102220450	BD-45 + 2 DD+32	22,2	500	544	16	22,2	25	300	180	45	200	110	32	19,7

Blueprint

