



Welded Master Link Assembly X-006W

Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Marking: According to standard, CE-marked

Standard: EN 1677-4

Safety factor: 4:1.

Класс: 10

| Код товара | Код | WLL ton | Proof Load kN | For chain gr 10 Ø 3-4 leg mm | Used to single hook acc. to DIN 15401 No. | D mm | A mm | B mm | d mm | a mm | b mm | Вес kg |
|--------------|-----------------|---------|---------------|------------------------------|---|------|------|------|------|------|------|--------|
| 402100420430 | CD-19 + 2 DD+13 | 4,2 | 103 | 6 | 6 | 19 | 160 | 95 | 13 | 54 | 25 | 1,5 |
| 402100820430 | CD-22 + 2 DD+16 | 8,2 | 201 | 7,8 | 10 | 22 | 170 | 105 | 16 | 70 | 34 | 2,3 |
| 402101070430 | CD-28 + 2 DD+19 | 10,7 | 262 | 10 | 10 | 28 | 190 | 110 | 19 | 85 | 40 | 4,1 |
| 402101570430 | CD-32 + 2 DD+22 | 15,7 | 385 | 13 | 12 | 32 | 230 | 130 | 22 | 115 | 50 | 6,6 |
| 402102220430 | CD-36 + 2 DD+28 | 22,2 | 544 | 16 | 20 | 36 | 275 | 150 | 28 | 140 | 65 | 10,9 |

Blueprint

