

## Electro galvanized shackles with locking DIN 82101



### Product information

Electro galvanized shackles approved for lifting.

**Marking:** CE-marked

**Safety factor:** 5:1

Код товара	WLL ton	Packing	d4 mm	b1 mm	d1 mm	d2 mm	h1 mm	Bec kg
420100040770	0,4	25	10	14	8	19	30	0,097
420100060770	0,6	25	12	17	10	21	36	0,18
420100100770	1	25	16	21	13	23	49	0,3
420100160770	1,6	25	20	27	17	26	61	0,57
420100200770	2	1	22	30	19	29	67	0,98
420100250770	2,5	1	24	33	21	33	73	1,3
420100320770	3	1	27	38	24	37	84	1,85
420100400770	4	1	30	42	27	41	91	2,53
420100500770	5	1	36	47	30	45	111	4
420100600770	6	1	39	53	34	55	120	5,3
420100800770	8	1	45	60	38	60	140	7,9
420101000770	10	1	48	66	42	65	147	10
420101600770	16	1	60	81	52	75	185	19,2
420102000770	20	1	68	90	58	80	211	28
420102500770	25	1	72	100	63	-	221	34
420103200770	32	1	80	110	70	-	246	49
420104000770	40	1	90	125	80	-	276	75

# Blueprint

