



Geared trolley

Product information

Geared trolley for IPE and T beams. The trolley moves on the beam by pulling the hand chain. The wheels are equipped with duration lubricated ball bearings. The width of the trolley can be adjusted by a threaded rod (10 and 20 t models with washers, in the picture). The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Marking: According to standard, CE-marked

Standard: EN 13157

Safety factor: 4:1

| Код товара | WLL ton | Beam width mm | Minimum radius mm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Bec kg |
|-----------------|---------|---------------|-------------------|-------|------|-------|------|------|------|------|------|--------|
| 502600102200130 | 1 | 58-220 | 700 | 353,5 | 238 | 183 | 17 | 31 | ~3 | 68 | 95 | 12,5 |
| 502600202200130 | 2 | 66-220 | 900 | 362 | 277 | 208 | 20 | 31 | ~3 | 80 | 108 | 17 |
| 502600302200130 | 3 | 74-220 | 1 200 | 406,5 | 324 | 249 | 26 | 31 | ~3 | 100 | 131 | 28 |
| 502600502200130 | 5 | 90-220 | 1 000 | 434,5 | 373 | 296,5 | 28 | 40 | ~5 | 120 | 154 | 45 |
| 502601002030130 | 10 | 125-203 | 1 300 | 487,5 | 455 | 490 | 82 | 36,5 | ~5 | - | - | 93 |
| 502602002030130 | 20 | 136-203 | 4 700 | 523 | 642 | 622 | 110 | 54 | ~5 | - | - | 247,5 |

Blueprint

