

## Accessories - 5 -10 Tons Cylinder

Product information



Код товара	Description
5297	• Suitable for HGC 5 and HGC 10• Max. working pressure: 720 bar• Standard supplied with 2x bolt M8x20 and 2x bolt M6x20
5297	• Suitable for HGC 5 cylinders• Thread size: 1½"-16 UN• Max. working pressure: 720 bar
5297	• To connect accessories to cylinders• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
5297	• To provide better grip• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar
5297	• For spreading• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar
5297	• Suitable for HGC 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar• Standard supplied with 2x bolt M8x16
5297	• To mount on bottom side of cylinder• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar
5297	• To connect 2 extension tubes• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female (2x)• Max. working pressure: 360 bar
5297	• Suitable for HGC 10 and HCJ 10 cylinders• Length: 125 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
5297	• Suitable for HGC 10 & HCJ 10 cylinders• Length: 250 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
5297	• Suitable for HGC 10 and HCJ 10 cylinders• Length: 500 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
5297	• Suitable for HGC 10 and HCJ 10 cylinders• Length: 750 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
5297	• Suitable for HGC 5 and HGC 10• Max. working pressure: 720 bar• Standard supplied with 2x bolt M8x20 and 2x bolt M6x20
5297	• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 144 bar
5297	• Suitable for HGC 10 cylinders• Thread size: 2¼"-14 UNS female• Max. working pressure: 144 bar
5297	• Suitable for HCJ 10 cylinders• Thread size: M60x2 female• Max. working pressure: 144 bar
5297	• Suitable for HCJ 10 cylinders• Thread size: 1¼" NPT female
5297	• Suitable for HCJ 10 cylinders• Thread size: 1¼" NPT male
5297	• Suitable for HGC 10 cylinders• Thread size: 2¼"-14 UNS• Max. working pressure: 720 bar