



Lifting Eye FP

Product information

Enormously flat lifting eye.

- The eyes can be loaded with working load limit in all directions and rotates 360°.
- Automatic locking link when folded.
- Secured four times against breakage in all load directions.
- Admissible working range of take-up link 110°.

Safety factor: 4:1

| Код товара | Код | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | Ø d mm | E mm | F mm | G mm | I mm | Øs mm | Bec kg |
|----------------|--------|---------|--------|-----------|------|------|------|--------|------|------|------|------|-------|--------|
| 42150381100000 | FP 0.5 | 0,5 | M10 | 60 | 69 | 50 | 48 | 13 | 28 | 100 | 12 | 52 | 34 | 0,71 |
| 42150381101000 | FP 0.8 | 0,8 | M12 | 90 | 69 | 50 | 48 | 13 | 28 | 100 | 17 | 51 | 34 | 0,73 |
| 42150381101500 | FP 1.5 | 1,5 | M16 | 160 | 69 | 50 | 48 | 13 | 28 | 100 | 27 | 49 | 34 | 0,77 |
| 42150381102100 | FP 2.5 | 2,5 | M20 | 420 | 69 | 50 | 48 | 13 | 33 | 103 | 37 | 44 | 41 | 0,92 |
| 42150381104200 | FP 4-S | 4 | M24 | 750 | 69 | 50 | 48 | 13 | 34 | 103 | 46 | 40 | 41 | 1,05 |
| 42150381104000 | FP 4 | 4 | M24 | 750 | 104 | 76 | 78 | 18 | 39 | 147 | 41 | 74 | 58 | 2,5 |
| 42150381105000 | FP 5 | 5 | M27 | 1 000 | 104 | 76 | 72 | 18 | 39 | 147 | 51 | 72 | 58 | 2,63 |
| 42150381106000 | FP 6 | 6 | M30 | 1 400 | 104 | 76 | 72 | 18 | 39 | 147 | 51 | 70 | 58 | 2,74 |
| 42150381108000 | FP 8 | 8 | M36 | 1 800 | 104 | 76 | 72 | 18 | 43 | 147 | 57 | 62 | 58 | 3,15 |

Blueprint

