



## Horizontal Lifting Clamp IPH10(J)

### Product information

#### General:

The IPH10(J) horizontal lifting clamps with spring loaded tension have a pretension feature that allows the user to attach the clamps to the material for horizontal lifting and transfer of non-sagging material. These clamps must be used in pairs or more.

#### Features:

- Available in capacities of .5 thru 12 metric tons.
- IPH10 type: jaw openings available: 0 to 60mm.
- IPH10J type: jaw openings available: 60 to 120mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Equipped with pretension system and handle for easy placement. Except 0.5t and 1t models.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

**Marking:** According to standard, CE-marked

**Standard:** EN 13155

<b>Код товара</b>	<b>WLL ton</b>	<b>Jaw width mm</b>	<b>Model</b>	<b>Вес kg</b>
502100050200170	0,5	0-20	0.5-IPH10*	1,8
502100100350170	1	0-35	1-IPH10*	2,5
502100200600170	2	0-60	2-IPH10	5,5
502100300600170	3	0-60	3-IPH10	7,5
502100301200170	3	60-120	3-IPH10J	9
502100450600170	4,5	0-60	4.5-IPH10	10,5
502100451200170	4,5	60-120	4.5-IPH10J	12
502100600600170	6	0-60	6-IPH10	13
502100601200170	6	60-120	6-IPH10J	15
502100900600170	9	0-60	9-IPH10	18,5
502100901200170	9	60-120	9-IPH10J	20,5
502101200600170	12	0-60	12-IPH10	21,5
502101201200170	12	60-120	12-IPH10J	24

# Blueprint

