



Endurance 50DB

Інформація про товар



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope
Flexibility is optimised by the unique strand and rope construction.
Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

Standard: EN 12385-4
ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Коефіцієнт заповнення: 0.64
RCN: 23-1

Код товару	Діаметр троса мм	Tensile strength N/mm ²	Покриття	Rope lay.	Мінімальна розривна сила кН 2160N/mm ²	Площа перерізу мм ²	Мастило	Вага kg/100m
102100806270139	8	1 960	Оцинковане	zZ	49,6	-	SupplierStandard	27,6
102100805270139	8	1 960	Оцинковане	sS	49,6	-	SupplierStandard	27,6
102100906270139	9	1 960	Оцинковане	zZ	62,8	-	SupplierStandard	34,4
102100905270139	9	1 960	Оцинковане	sS	62,8	-	SupplierStandard	34,4
102101006270139	10	1 960	Оцинковане	zZ	77,6	-	SupplierStandard	42,5
102101005270139	10	1 960	Оцинковане	sS	77,6	-	SupplierStandard	42,5
102101106270139	11	1 960	Оцинковане	zZ	93,9	-	SupplierStandard	51,8

102101105270139	11	1 960	Оцинковане	sS	93,9	-	SupplierStandard	51,8
102101206270139	12	1 960	Оцинковане	zZ	112	-	SupplierStandard	61,9
102101205270139	12	1 960	Оцинковане	sS	112	-	SupplierStandard	61,9
102101306270139	13	1 960	Оцинковане	zZ	131	-	SupplierStandard	72,8
102101305270139	13	1 960	Оцинковане	sS	131	-	SupplierStandard	72,8
102101406270139	14	1 960	Оцинковане	zZ	152	-	SupplierStandard	83,6
102101405270139	14	1 960	Оцинковане	sS	152	-	SupplierStandard	83,6
102101506270139	15	1 960	Оцинковане	zZ	175	-	SupplierStandard	96
102101505270139	15	1 960	Оцинковане	sS	175	-	SupplierStandard	96
102101606270139	16	1 960	Оцинковане	zZ	199	-	SupplierStandard	110
102101605270139	16	1 960	Оцинковане	sS	199	-	SupplierStandard	110
102101706270139	17	1 960	Оцинковане	zZ	224	-	SupplierStandard	121
102101705270139	17	1 960	Оцинковане	sS	224	-	SupplierStandard	121
102101806270139	18	1 960	Оцинковане	zZ	251	-	SupplierStandard	136
102101805270139	18	1 960	Оцинковане	sS	251	-	SupplierStandard	136
102101906270139	19	1 960	Оцинковане	zZ	280	-	SupplierStandard	156
102101905270139	19	1 960	Оцинковане	sS	280	-	SupplierStandard	156
102102006270139	20	1 960	Оцинковане	zZ	310	-	SupplierStandard	168
102102005270139	20	1 960	Оцинковане	sS	310	-	SupplierStandard	168
102102106270139	21	1 960	Оцинковане	zZ	342	-	SupplierStandard	185
102102105270139	21	1 960	Оцинковане	sS	342	-	SupplierStandard	185
102102206270139	22	1 960	Оцинковане	zZ	375	-	SupplierStandard	206
102102205270139	22	1 960	Оцинковане	sS	375	-	SupplierStandard	206