

Wire rope DSC8

Інформація про товар



Typical applications: When a high MBL is required for a multipart reeving hoist system: electric hoists, twin hoist systems (right and left ropes), boom hoist and pendant rope for mobile cranes and tower cranes.


Fill factor: 10 mm - 0,74, 11-32 mm - 0,73, 33-50 mm - 0,71.

Standard: EN 12385-4

ISO 4309 Rope Category No: 10mm RCN.04, 11-22mm RCN.09, 24-50mm RCN.11

RCN: 04

Overhead cranes



Tower crane



Mobile port crane



Offshore crane



Crawler crane



Container crane



Код товару	Діаметр троса мм	Tensile strength N/mm ²	Площа перерізу мм ²	Мінімальна розривна сила кН 2160N/mm ²	Покриття	Вага kg/100m
103101004070099	10	1 960	-	-	Неоцинковане	-

103101104070099	11	1 960	-	-	Неоцинковане	-
103101204070099	12	1 960	-	-	Неоцинковане	-
103101304070099	13	1 960	-	-	Неоцинковане	-
103101404070099	14	1 960	-	-	Неоцинковане	-
103101504070099	15	1 960	-	-	Неоцинковане	-
103101604070099	16	1 960	-	-	Неоцинковане	-
103101704070099	17	1 960	-	-	Неоцинковане	-
103101804070099	18	1 960	-	-	Неоцинковане	-
103101904070099	19	1 960	-	-	Неоцинковане	-
103102004070099	20	1 960	-	-	Неоцинковане	-
103102204070099	22	1 960	-	-	Неоцинковане	-
103102404070099	24	1 960	-	-	Неоцинковане	-
103102604070099	26	1 960	-	-	Неоцинковане	-
103102804070099	28	1 960	-	-	Неоцинковане	-
103103004070099	30	1 960	-	-	Неоцинковане	-
103103204070099	32	1 960	-	-	Неоцинковане	-
103103404070099	34	1 960	-	-	Неоцинковане	-
103103604070099	36	1 960	-	-	Неоцинковане	-
103103804070099	38	1 960	-	-	Неоцинковане	-
103104004070099	40	1 960	-	-	Неоцинковане	-
103104204070099	42	1 960	-	-	Неоцинковане	-
103104404070099	44	1 960	-	-	Неоцинковане	-
103104604070099	46	1 960	-	-	Неоцинковане	-

103104804070099	48	1 960	-	-	Неоцинковане	-
103105004070099	50	1 960	-	-	Неоцинковане	-

Креслення