



Wire rope Dyform 6

Інформація про товар



Superior bending fatigue life when compared with conventional six strand crane ropes.
Excellent resistance to crushing and abrasion particularly on multi-layer coiling resulting from the Dyform strands.
Reduced elongation results from increased steel content and the Dyform process.
Optional plastic impregnation to further extend fatigue life, improve structural stability and resistance to corrosion.

ISO 4309 Rope Category No: 8-15mm **RCN.06**, 16-46mm **RCN.09**, 48-50mm **RCN.11**

Маркування: Згідно зі стандартом

Стандарт: EN 12385-4

Коефіцієнт заповнення: 0.64

RCN: 06

Код товару	Діаметр троса мм	Tensile strength N/mm ²	Мінімальна розривна сила кН 2160N/mm ²	Покриття	Вага kg/100m
103101004270509	10	1 960	-	Оцинковане	-
103101104070509	11	1 960	-	Неоцинковане	-
103101204070509	12	1 960	-	Неоцинковане	-
103101304070509	13	1 960	-	Неоцинковане	-
103101404070509	14	1 960	-	Неоцинковане	-
103101504070509	15	1 960	-	Неоцинковане	-
103101604070509	16	1 960	-	Неоцинковане	-

103101704070509	17	1 960	-	Неоцинковане	-
103101804070509	18	1 960	-	Неоцинковане	-
103101904070509	19	1 960	-	Неоцинковане	-
103102004070509	20	1 960	-	Неоцинковане	-
103102204070509	22	1 960	-	Неоцинковане	-
103102404070509	24	1 960	-	Неоцинковане	-
103102504070509	25	1 960	-	Неоцинковане	-
103102604070509	26	1 960	-	Неоцинковане	-
103102804070509	28	1 960	-	Неоцинковане	-
103103004070509	30	1 960	-	Неоцинковане	-
103103204070509	32	1 960	-	Неоцинковане	-
103103404070509	34	1 960	-	Неоцинковане	-
103103604070509	36	1 960	-	Неоцинковане	-
103103804070509	38	1 960	-	Неоцинковане	-
103104004070509	40	1 960	-	Неоцинковане	-
103104204070509	42	1 960	-	Неоцинковане	-