



## Wire Rope Hydra Plus

### Інформація про товар



The Hydra is a range of high performance multi strand low rotational ropes for offshore oil and gas applications including offshore cranes, winches, and A&R lines.

- Engineered low rotational characteristics
- Dyform construction for crush & wear resistance
- Enhanced radial stiffness
- Recommended for multilayer spooling
- Low elongation

RCN: 23-2

Відхилення Ø: 0% to +2%

Код товару	Діаметр троса мм	Мінімальна розривна сила кН 2160Н/мм <sup>2</sup> 1960 Н/мм <sup>2</sup>	Мінімальна розривна сила кН 2160Н/мм <sup>2</sup> 2160 Н/мм <sup>2</sup>	Вага кг/м
104105086270499	50,8	2330	2450	12,8
104105206270499	52	2450	2560	13,5
104105406270499	54	2640	2760	14,5
104105606270499	56	2840	2970	15,6
104106006270499	60	3250	3410	17,9
104106206270499	62	3480	3640	19,1
104106406270499	64	3700	3880	20,4

104106606270499	66	3940	4120	21,7
104106806270499	68	4180	4380	23
104107006270499	70	4430	4640	24,4
104107206270499	72	4680	4910	25,8
104107406270499	74	4950	5180	27,2
104107606270499	76	5220	5470	28,7
104107806270499	78	5490	5760	30,3
104108006270499	80	5780	6060	31,8
104108206270499	82	5890	6170	32,3
104108406270499	84	6180	6480	33,9
104108606270499	86	6480	6790	35,6
104108806270499	88	6780	7110	37,3
104109006270499	90	7100	7430	39
104109206270499	92	7420	7770	40,7
104109606270499	96	8070	8450	44,3
104109806270499	98	8410	8810	46,2
104110206270499	102	9170	9600	50,4
104110606270499	106	9910	10370	54,4
104110806270499	108	10270	10760	56,5
104111006270499	110	10660	11160	58,7
104111606270499	116	11840	-	65,2
104112206270499	122	13100	-	72,2
104112406270499	124	13530	-	74,5

104112806270499	128	14410	-	79,4
104113006270499	130	14870	-	81,9
104113506270499	135	15290	-	88,4
104113806270499	138	15980	-	92,3
104114206270499	142	16910	-	97,8
104114606270499	146	17870	-	103
104115006270499	150	18850	-	109
104115206270499	152	19350	-	112