



Wire Rope Clip with Forged Bridge POWERTEX PCTB

Інформація про товар



The Powertex Wire Rope Clip with Forged Bridge PCTB is suitable for suspending static loads and single-use lifting operations. Available in sizes from 6 to 40 mm, this wire rope clip is designed and tested in accordance with the EN 13411-5B standard, ensuring compliance and reliability in every use.

Product benefits

- **Safety Compliance:** These wire rope clips comply with EN 13411-5B standards, meeting stringent safety and quality requirements.
- **Superb Grip:** The bridge features distinctive friction ridges that increase friction between the bridge and the wire rope, ensuring a secure grip where the rope makes contact with the bridge.
- **High Load Capacity:** When correctly mounted, the assembly can withstand up to 80% of the rope's minimum breaking load (MBL), providing robust and reliable performance.
- **Compatibility:** Designed for use with six-stranded right-hand lay ropes in 6x19 (M) and 6x36 classes and right-hand lang's lay wire rope in 8x19 class up to 1960 N/mm², with fibre core and a steel core.
- **Durable Finish:** Electro Galvanized (Chrome 6 Free)
- **Full Traceability:** Every Wire Rope Clip is marked with Powertex or PX branding, Max Rope Size (Inch), and a traceability code, ensuring traceability to the production lot and raw materials.

Креслення

