



Heavy Duty Air Chain Hoists Red Rooster TMH (10.000, 15.000 & 20.000 kg)

Інформація про товар

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a supporting eye for easy installation.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Маркування: Згідно зі стандартом, CE-marked

Стандарт: EN 14492-2

Код товару	Вантажопідйомність тон	Тип	Chain falls	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Швидкість підйому м/хв	Lowering speed with max.load m/min	Швидкість підйому м/хв	A B C D E F G H I J K L M N	Bara кг
5601TMH10TC2	10	Cord control	2	71,7	58,3	1,6	3,2	3,3	860 463 188 275 221 60 214 266 315 65	∅60 45 351 ∅61 206
5601TMH10TP2E	10	Pendant control	2	71,7	58,3	1,6	3,2	3,3	860 463 188 275 221 60 214 266 315 65	∅60 45 351 ∅61 206
5601TMH15C3	15	Cord control	3	71,7	58,3	1,05	2,1	2,2	880 695 635 255 270 52 250 266 315 67	∅84 58 436 ∅84 316
5601TMH15P3E	15	Pendant control	3	71,7	58,3	1,05	2,1	2,2	880 695 635 255 270 52 250 266 315 67	∅84 58 436 ∅84 316
5601TMH20C4	20	Cord control	4	71,7	58,3	0,8	1,6	1,6	1 028 500 150 350 - 64 315 326 387 80	∅110 78 475 ∅110 466
5601TMH20P4E	20	Pendant control	4	71,7	58,3	0,8	1,6	1,6	1 028 500 150 350 - 64 315 326 387 80	∅110 78 475 ∅110 466

Креслення

