



Lifting Point POWERTEX LPB

Інформація про товар

Elevate your lifting operations with the POWERTEX Lifting point with ball bearing link - LPB, a state-of-the-art solution tailored for the demanding requirements of industrial environments. The LPB is designed to offer unparalleled flexibility with the ability to rotate 360 degrees and pivot +/- 115 degrees, making it perfect for scenarios requiring a wide range of motion. Crafted with a forged housing with a hexagon-shaped grip, the LPB ensures quick and secure mounting using standard tools. Its distinctive feature is the ability to rotate under full load smoothly, thanks to the integrated ball bearing, providing fluid movement and robust operation.

Allowed Loading directions:

- o 360° rotation, +/- 115° pivot motion
- o WLL According to WLL Diagram
- o The LPB is designed to rotate under load

Product Features:

- **Durable finish:** Coated in PURE RED powder paint, the LPB lifting points stand out for their durability and corrosion resistance.
- **Compliance to standard:** Manufactured to meet the testing requirements specified by EN 1677-1, ensuring high safety and quality standards.
- **Reliable:** Designed with a safety factor of at least 4 in the intended load directions, offering a secure lifting experience.
- **Quality assurance:** Each component undergoes crack detection testing in the factory and all forged links are proof load tested to ensure reliability.
- **Type testing:** Each model undergoes factory type testing including breaking tests and fatigue test to 20,000 cycles at 1.5 times the WLL, highlighting the product's endurance.
- **Full traceability:** Every component is marked with POWERTEX branding, model name, WLL, CE-mark, UKCA-mark, and a traceability code, ensuring traceability to the production lot and raw materials.
- **WLL indication:** The LPB is marked with the lowest WLL at 90° as the general WLL. The WLL chart provides a higher WLL for straight vertical loading.
- **Harmless:** Chromium 6 free, aligning with environmental safety standards.
- **Certificates included:** Comes with a POWERTEX 2.2 certificate & Declaration of Conformity with each box, confirming compliance with EC and UK regulations.
- **Wide temperature range:** Optimized for use between -40°C to +200°C without WLL reduction, with permissible WLL reductions for

higher temperature ranges, ensuring adaptability to various environments.

Маркування: Згідно зі стандартом, CE-marked, UKCA-marked

Стандарт: EN 1677-1

Код товару	Вантажопідйомність тон	Thread mm	Модель	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	T mm	Вага кг
4215LPBM8	0,4	M8	LPB-M8	10-40	12	44	30	40	37	12	46	98	0,44
4215LPBM10	0,6	M10	LPB-M10	10-40	12	44	30	40	37	19	46	98	0,45
4215LPBM12	0,7	M12	LPB-M12	15-40	12	44	30	40	37	19	46	98	0,45
4215LPBM16	1,5	M16	LPB-M16	45-130	12	44	30	40	37	31,8	46	98	0,5
4215LPBM20	2,5	M20	LPB-M20	100-170	20	67	40	70	64,3	38,1	76	160	2,3
4215LPBM24	4	M24	LPB-M24	190-280	20	67	40	70	64,3	38,1	76	160	2,4
4215LPBM30	6	M30	LPB-M30	270-600	22	95	51	79	74	50	91	206	3,8
4215LPBM36	10	M36	LPB-M36	270-600	22	95	51	79	74	54	91	206	3,9
4215LPBM42	13	M42	LPB-M42	350-800	26	108	65	93	85	63	100,5	230,5	6
4215LPBM48	14	M48	LPB-M48	350-800	26	108	65	93	85	68	100,5	230,5	6,2
4215LPBM56	20	M56	LPB-M56	350-900	32	120	70	105	95	84	132	278	10,1
4215LPBM64	20	M64	LPB-M64	500-1000	32	120	70	105	95	95	132	278	10,9

Креслення

