

Аксесуари для циліндрів 5-10 тонн

Інформація про товар



| Код товару | Description |
|------------|---|
| 5297 | • Suitable for HGC 5 and HGC 10• Max. working pressure: 720 bar• Standard supplied with 2x bolt M8x20 and 2x bolt M6x20 |
| 5297 | • Suitable for HGC 5 cylinders• Thread size: 1½"-16 UN• Max. working pressure: 720 bar |
| 5297 | • To connect accessories to cylinders• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar |
| 5297 | • To provide better grip• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar |
| 5297 | • For spreading• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar |
| 5297 | • Suitable for HGC 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar• Standard supplied with 2x bolt M8x16 |
| 5297 | • To mount on bottom side of cylinder• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar |
| 5297 | • To connect 2 extension tubes• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female (2x)• Max. working pressure: 360 bar |
| 5297 | • Suitable for HGC 10 and HCJ 10 cylinders• Length: 125 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar |
| 5297 | • Suitable for HGC 10 & HCJ 10 cylinders• Length: 250 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar |
| 5297 | • Suitable for HGC 10 and HCJ 10 cylinders• Length: 500 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar |
| 5297 | • Suitable for HGC 10 and HCJ 10 cylinders• Length: 750 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar |
| 5297 | • Suitable for HGC 5 and HGC 10• Max. working pressure: 720 bar• Standard supplied with 2x bolt M8x20 and 2x bolt M6x20 |
| 5297 | • Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 144 bar |
| 5297 | • Suitable for HGC 10 cylinders• Thread size: 2¼"-14 UNS female• Max. working pressure: 144 bar |
| 5297 | • Suitable for HCJ 10 cylinders• Thread size: M60x2 female• Max. working pressure: 144 bar |
| 5297 | • Suitable for HCJ 10 cylinders• Thread size: 1¼" NPT female |
| 5297 | • Suitable for HCJ 10 cylinders• Thread size: 1¼" NPT male |
| 5297 | • Suitable for HGC 10 cylinders• Thread size: 2¼"-14 UNS• Max. working pressure: 720 bar |