

Трубопровідна арматура



Інформація про товар

Трубопровідна арматура

| Код товару | Модель | Description |
|------------|---------|--|
| 5297 | A 109 N | • For accurate control of the oil flow, also under maximum pressure. • Connection: 3/8" NPT female (2x). |
| 5297 | A 195 | • Very suitable for quick shut-off valve (open/close). • Can be operated under maximum pressure. • Connection: 3/8" NPT female (2x). |
| 5297 | A 130 | • For accurate control of the oil flow, also under maximum pressure. • Connection: 3/8" NPT male and 3/8" NPT female. |
| 5297 | A 110 | • Protects against sudden pressure drop in the supply pipe, for example in case of hose rupture. • To be mounted between pump and cylinder as close to the cylinder as possible. • Provided with pressure relief valve, set at 830 bars. • While pumping: valve closed, safety valve active. • For relief: open valve, safety valve not active. • Connection: 3/8" NPT female and 3/8" NPT male. |
| 5297 | A 134 N | • Suitable for hose rupture security. • Not to be used with double-acting systems. • Connection: 3/8" NPT, male. • Fits: A 119. |
| 5297 | A 209 | • Spring-loaded. • Connection: 3/8" NPT male (2x). |
| 5297 | A 135 | • Set to 750 bars. • Connection: 1x 3/8" NPT female and 1x 3/8" NPT male. |